



AEROTAPE®

FOR ALL KINDS OF
AIR CONDITIONERS

ENERGY SAVING
PREVENTS CONDENSATION
EASY TO USE
ADHERES TO ALL METALS

FOR ALL KINDS OF
CONDITIONERS

FOR ALL KINDS OF
AIR CONDITIONERS

ENERGY SAVING
PREVENTS CONDENSATION
EASY TO USE
ADHERES TO ALL METALS

TOP

Insulation and Trading

AEROTAPE®

The High Quality Self Adhesive
Insulation Foam Tape

AEROTAPE[®]

The High Quality Self Adhesive Insulation Foam Tape



AEROTAPE[®] is the flexible and self-adhesive insulation foam tape, which is made from the same elastomeric material as AEROFLEX Closed Cell Insulation.

Ideal for wrapping hot or cold pipings and fittings. Energy saving and very easy to use. Excellent for preventing condensation problems. Designed specially for retarding heat loss in hot pipings and preventing heat gain or frost formation on cold, chilled water pipings or refrigeration lines.


Adheres firmly to all metals. No problem of delamination. AEROTAPE is specially coated with selected acrylic pressure sensitive adhesive providing long service life.

SPECIFICATION :

Size : 1/8" thick, 2" wide and 30' long per roll
(3 mm.x 50 mm.x 9.1 m.) \pm 3%
(other sizes available upon request.)

PACKING :

One roll of Aerotape wrapped in a plastic bag and packed in one individual box. (10 boxes in one carton)



PHYSICAL PROPERTIES :

Composition	: Closed cell, elastomeric thermal insulation. Same material as AEROFLEX Insulation Tubes and Sheets.
Color	: Black
Density	: 5 \pm 1pounds per cubic feet. (0.06-0.10 g/cm ³) ASTM D-1667
Thermal Conductivity	: 0.26 BTU. in/ft ² hr. °F at 75 °F (0.04 W/mk at 24 °C) (ASTM C-177)
Water Absorption	: Max. 5% by weight (ASTM D-1056)
Water Vapor Permeability	: 0.12 Perm-inch. (ASTM C-355)
Temperature Range	: -20 °F (-29 °C) to + 200 °F (+93 °C)

THICKNESS TO PREVENT CONDENSATION:

Ambient Temperature and Relative Humidity	Pipe Temperature	
	50 °F (10 °C)	35 °F (2 °C)
80 °F (27 °C) & 50% RH	Single Layer	50% Overlap
85 °F (30 °C) & 70% RH	50% Overlap Plus Single Layer	50% Overlap Plus 50% Overlap

TOP
Insulation and Trading

บริษัท ทีโอพี อินซูเลชัน แอนด์เทรดดิ้ง จำกัด
7/1 ซอยพหลโยธิน 108 หมู่ 9 แขวงจตุจักร
เขตจตุจักร กรุงเทพฯ 10160
Tel. 02 808 2147-8 Fax. 02 808 3457